

The Pro's Choice Since 1936

SAKRETE®

Concrete Cure'n Seal

PRODUCT # 19064

A highly water-resistant, water-based clear liquid acrylic copolymer coating that dries to a semi-gloss finish. SAKRETE Cure'n Seal helps protect and seal concrete surfaces from grease, salts and acids and improves the ability of the concrete to repel water. Meets ASTM Specification C 309 when used as directed. For the curing and sealing of concrete driveways, garage floors, loading docks, patio pavers and sidewalks. **READY TO USE, DO NOT DILUTE.**

SAFETY:

READ and UNDERSTAND the Material Safety Data Sheet (MSDS) before using this product. **WARNING:** Wear protective clothing and equipment. See HMIS block. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA). **KEEP OUT OF REACH OF CHILDREN.**

PREPARATION:

Curing:

When used as a curing compound don't apply if the temperature is below 50° F (10° C), or if rain, dew or fog is forecast within 24 hours.

Sealer:

When used as a sealer, remove all loose and foreign material such as oil and dirt. Do not apply as a sealer if rain, dew, fog or temperatures below 50° F (10° C) are forecast within 4 hours.

PLACEMENT:

Curing:

When used as a curing agent, apply undiluted after the new concrete has hardened and the surface water and sheen have disappeared, usually about 4 to 6 hours after placing. In hot weather, the time to apply may be reduced to 2 to 3 hours after the concrete is placed. For best results, apply in 2 even, thin applications at right angles to each other, using a pump-up pressure sprayer. Apply at the rate of 200 sq. ft. per gal (4.9 sq. m/L). Do not puddle the Cure 'n Seal. Even application is particularly important when applying over colored concrete.

Sealer:

When used as a sealer, remove all loose and foreign materials such as oil and dirt. Do not apply as a sealer if rain, dew, fog or temperatures below 50° F (10° C) are forecast within 4 hours. Clean tools with soapy water immediately after application.

Drying time: Cure 'n Seal dries by evaporation. Under most conditions it will dry in about 1 hour, but cool, damp weather or hot, humid weather will extend the drying time. Do not cover the area treated with Cure 'n Seal for at least 24 hours. VOC LIMIT: 700 g/l

Curing: Reduces the need for wet curing in warm, dry, windy weather. Improves strength, wear resistance and durability, while reducing shrinkage.

STORAGE:

STORAGE: Store in a tightly closed container off the floor in a dry place. **KEEP FROM FREEZING.**

COVERAGE:

Approximately 200 sq. ft. per gallon

PACKAGING:

1 Gallon (3.8 L) UPC: 7-64661-19064-6

ENVIRONMENTAL ADVISORY:

Uncured or crushed cured cement is an environmental hazard, which may adversely affect fish and wildlife. Dispose of construction debris containing cement, including empty bags, at a permitted municipal disposal firm. Do not use crushed concrete as a fill near an aquatic habitat.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, wash thoroughly with plenty of soap and water. If irritation persists, get medical attention. If vapors or fumes are inhaled, remove person to fresh air. If swallowed, give plenty of water and call a Physician immediately. **DO NOT INDUCE VOMITING.**

CAUTION: Vapors may cause irritation of eyes, nose and throat. May cause skin sensitization or other allergic responses. **HARMFUL IF SWALLOWED.** Do not breathe vapors. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use. Do not transfer to unmarked container.

LIMITED PRODUCT WARRANTY The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. **ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY.** Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. **CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.**

The SAKRETE Companies
866-SAKRETE
866-725-7383
www.sakrete.com